

security labs

Features (SLC-1035 B/W)

- Camera type: 1/3" B/W CCD
- Video: NTSC, composite 1V p-p, 75 ohm
- Light sensitivity: 0.3 LUX
- Iris: auto electronic
- Resolution: 420 lines
- Lens: 3.6mm, pre-focused
- Power: 12VDC, 125 ma, 2.1mm jack
- Weight: 4 ounces
- Diameter: 5.5"
- Height: 1.75"
- Connections: RCA type video jack
- Kit includes:
 - 12VDC power supply
 - 50' video-power cable
 - Mounting hardware
 - 9VDC battery (smoke detector operation)



SLC-1035 B/W Covert Camera

The SLC-1035 is designed for high performance covert surveillance. Housed in a **working & UL listed** smoke detector housing is our high resolution (420) line CCD board camera. Designed for ceiling mount installations, the viewing angle of the camera is at a 45 degree angle to the mounting plane. A wide angle (3.6mm) lens provides a 18' vertical by 24' horizontal viewing range at 20'.

Lightweight and easily mounted, the camera kit includes a power adapter, 50' video-power cable, and mounting hardware. The integrated video-power cable allows the installer to place the power adapter at the end of the cable run (at the monitor, recorder, or multiplexer). The video connection is terminated with a RCA type connector to facilitate connection to monitors, recorders, or televisions with a video in jack.

SLC-1035C Color Covert Camera

Identical in appearance and mounting characteristics to the SLC-1035 (above). A Sony Super HAD imager provides superb color picture clarity.



Features (SLC-1035C Color)

- Camera type: 1/4" color Super HAD CCD
- Video: NTSC, composite 1V p-p, 75 ohm
- Light sensitivity: 0.5 LUX
- Iris: auto electronic
- Resolution: 330 lines
- Lens: 3.7mm, pre-focused
- Power: 12VDC, 120 ma, 2.1mm jack
- Weight: 4 ounces
- Diameter: 5.5"
- Height: 1.75"
- Connections: RCA type video jack
- Kit includes:
 - 12VDC power supply
 - 50' video-power cable
 - Mounting hardware