

SLC-115

B/W CCTV Camera

security labs

Features

- Camera type: 1/3" B/W CCD
- Video: NTSC, composite 1V p-p, 75 ohm
- Light sensitivity: .3 LUX
- Iris: auto electronic w/ auto iris lens connector
- Resolution: 420 lines
- Lens: 4mm wide angle, adjustable focus
- Power: 12VDC, 150 mA, 2.1mm jack, red LED
- Size: 2"W x 2"H x 4"D; 4 ounces
- Connections: RCA type video/audio, 2.1mm DC jack
- Temperature Range: 10 to 130 Deg. F.
- Audio: internal condenser mic
- Electronic shutter: switchable ON/OFF
- Kit includes:
 - 12VDC power supply
 - 50' audio-video-power cable
 - Swivel mount
 - Mounting hardware



SLC-115 Standard Body B/W CCTV Camera

A perfect choice for any system requiring clear, crisp images is the SLC-115 B/W CCD camera. Features include a external 4 pin auto iris connector, switchable electronic shutter, a sensitive internal condenser mic, and a 1/4" x 20 mount that is movable from the bottom of the camera to the top. A red LED on the front of the camera indicates power.

The 4mm wide angle lens will generate a view that is 18' vertical and 24' horizontal at a distance of 20' from the camera.

The SLC-115 kit includes a power supply, 50' of audio-video-power cable, a swivel mounting bracket for adjustable viewing, and mounting hardware.

Additional lenses for the SLC-115:

SLL170: 8mm lens. Generates a view that is 9' vertical and 12' horizontal at 20' from the camera.

SLL175: 12mm lens. Generates a view that is 6' vertical and 8' horizontal at 20' from the camera.