

SLC-135V

Varifocal B/W Bullet Camera

security labs

Features

- Camera type: 1/3" CCD B/W
- Video: NTSC, composite 1V p-p, 75 ohm
- Light sensitivity: 0.1 LUX
- Iris: auto electronic
- Resolution: 380 lines
- Lens: varifocal 4mm to 9mm
- Power: 12VDC, 110 mA, 2.1mm jack
- Weight: 6 ounces
- Size: 4" length x 1" diameter
- Audio: internal condenser mic
- Connections: RCA male video plug, 2.1mm DC jack
- Temperature Range: 10 to 130 Deg. F.
- Kit includes:
 - 12VDC power supply
 - 50' audio-video-power cable
 - Swivel mounting bracket & hardware



SLC-135V Varifocal Bullet Camera

Ideal for installations where just one camera lens won't do, the SLC-135V is equipped with a wide angle to telephoto varifocal lens. The user can manually change the focal length (zoom factor) of the camera in environments where the area under surveillance changes or is unknown before installation. Sensitive to low light (.1 LUX) allows this versatile camera to see in less than perfect conditions.

At a typical distance of 20' from the camera, the lens can be adjusted to display an area 24' horizontally x 18' vertically (4mm lens setting) or zoomed in to a 11' horizontal to 8' vertical view (9mm setting). The SLC-135V is supplied with an adjustable swivel mount, regulated power supply, hardware, and 50' of video/power cable.