

security labs

Features

- 14" color monitor with built in real time quad and IR remote
- Includes one SLC-148C color motorized pan & tilt dome camera with audio. Also included is 65' of cable and dome camera flush mount hardware. Controls on the front of the monitor allow for panning the camera 360 degrees and tilting 90 degrees. Pan & tilt can be performed in quad or full screen mode.
- Cameras can be auto sequenced with adjustable dwell time.
- On screen time and date / titling for each camera.
- Monitor has separate six pin DIN & BNC video inputs for flexibility in connecting cameras.
- Full function IR remote included for programming, and control of pan & tilt camera(s).
- Alarm inputs for each camera allow a motion detector or similar device to alarm the monitor. Monitor alarm outputs for VCR recording or other device activation. Automatic alarm operation available with the Security Labs SLC-132C and SLC-133C weatherproof cameras with built in passive infrared motion detection.
- Digital video storage feature records up to 12 frames of video that can be played back with a touch of a button. Digital frame capture can be initiated manually or programmed to capture a defined number of frames when an alarm occurs.
- Slave monitor output for remote viewing on another monitor.
- Selectable VCR output allows the user to record a continuous quad image or the active image on the monitor.
- Multiple image display arrangements including quad and PIP (picture in picture).
- Selectable background and border colors.
- Security lock function, video loss alarm.
- Power supply 100 to 240VAC, 50/60 Hz.
- NTSC standard; convertible to PAL format.
- 420 lines of horizontal resolution for a crisp picture.
- Dimensions 14.4"W x 13.5"H x 13.5"D; Weight: 29 lbs.



Dome camera pan & tilt controls and programming menus are easily accessed from the front panel

Accessories for the SLM418C

SLB220
Wall Mount



SLB220
Ceiling Mount



Weatherproof Dome Mounts
These high quality mounting brackets protect the SLC-148C for use indoor or outdoors. Both the ceiling and wall mount styles include heavy duty stainless steel mounting hardware.



SLC148C: Additional motorized pan & tilt color dome camera that is identical to one included with the monitor. Includes flush mount ceiling hardware and 65' cable. Up to three cameras can be added (four total in system).

Six Pin DIN Camera Extension Cables
For use with the SLC-148C, SLC-132C, & SLC-133C color cameras

SLA10: 65' cable with connection adapter
SLA11: 131' cable with connection adapter
SLA12: 198' cable with connection adapter



The maximum cable length must not exceed 200' when using SLC-148C pan & tilt dome cameras. The 200' limit includes extension cables.