

SLM419

12" B/W Quad Observation System

security labs

Features

- 12" B/W high resolution monitor with built in quad processor - view up to four cameras on screen
- Included with the monitor is one SLC-143 B/W 1/3" weatherproof CCD camera with PIR/Audio/IR illumination/Two Way Audio Intercom to camera. The PIR (passive infrared motion detector) incorporates industrial grade components and the latest technology in indoor or outdoor motion detection. The camera has built in infrared illumination that can see in total darkness (minimum range is 10'). Camera is equipped with a 3.7mm fixed lens which has a 92 degree angle of view. Also included is a wall or ceiling mounting bracket, 50' of cable, and hardware
- Sequential switcher rotates images between cameras in adjustable increments
- Horizontal resolution: 800 lines at center
- Audio and video outputs for recorder connections
- Additional slave audio and video output for remote monitoring
- Main and standby power switches
- Switchable alarm function alerts monitor when motion is detected in front of any camera (PIR)
- Alarm outputs on monitor can trigger a recorder or other device with a normally open or closed contact.
- Alarm inputs can be used for cameras without a built in motion detector
- Any connected VCR can be monitored live to ensure recording status
- Dimensions: 12.5"W x 12"D x 12"H



Accessories for the SLM419

SLC-143: Additional weatherproof camera. One SLC-143 is included with the monitor. Up to three cameras can be added (four total in system). Includes 50' cable.



SLA30: This adapter allows connection of any standard composite video CCTV camera to the SLM417 or SLM419 monitor. The adapter converts the 6 pin mini DIN camera input jack on the back of the monitor to two RCA jacks (one audio, one video). One SLA30 adapter is required for each camera. The SLC-142 and SLC-143 do not require an adapter.



SLC-142: Black case weatherproof camera that is identical in features to the SLC-143 (included with the monitor). Up to three cameras can be added (four total in system).



Camera Cable Extensions

These extension cables will work with the SLC-142 or SLC-143:

- SLA10:** 65' cable with connection adapter
- SLA11:** 131' cable with connection adapter
- SLA12:** 198' cable with connection adapter
- SLA13:** 328' cable with connection adapter