

SRS-506

Dual Stream Pentaplex Internet-3G DVR and Camera System

security labs



Features:

- SLD266 - 16 CH Internet DVR w 500 GB HD (up to 3 Terabyte internal expansion)
- Dual stream H.264 codec for both high quality recording & high speed network transmission
- Pentaplex Operation: Live display, record, backup, playback, & network access simultaneously
- Back panel port for additional eSATA external hard drive
- 22 x 15 (330 point) grid video motion detection per channel
- Nine criteria items to search for events per channel
- 16MB of pre-alarm storage per event (approximately 10 seconds before event happens)
- Individual setup of resolution, frame rate and video quality for each channel
- Picture-in-picture monitoring and 2X to 8X digital zoom display
- Control Methods: Front panel, USB mouse, IR remote, & PC client viewer
- Intuitive GUI for easy configuration and menu driven operation
- Still image snapshot and portable video (AVI) converter with time stamp
- Pan / Tilt / Zoom camera control, multi-language OSD
- Two USB ports (for mouse usage and backup)
- Data backup via: USB devices, network, and optional DVD-RW
- E-mail notification & event trigger for motion detection, alarm, and video loss
- **MyDVRView™**: Connect to the DVR from **any internet device** with a browser, no software needed, 3G smartphone ready
- Includes optical mouse, IR remote, additional viewing and control PC software, LAN & BNC video cable, & power supply
- **CAMERAS:** (16) SLC-3130 weatherproof IR CCD bullet cameras, 420 lines, 3.6mm wide angle lens; (4) simulated dome cameras add the appearance of additional surveillance at your location. Included are (16) 50' video power cables, mounts, mounting hardware, and window-door warning decals.



SRS-506

Dual Stream Pentaplex Internet-3G DVR and Camera System

security labs



Security Labs DVR Model	SLD266: 16 CH	SLD265: 8 CH	SLD264: 4 CH
CONNECTIONS			
Video System	NTSC / PAL switch		
Video Input	16CH BNC	8CH BNC	4CH BNC
Video Output	1CH BNC		
SPOT Output	1CH BNC		
VGA Output	1024x768		
Audio Input	4CH RCA	4CH RCA	1CH RCA
Audio Output	1CH RCA		
Audio Backup	YES		
Sensor	16 input / 2 output	8 input / 1 output	4 input / 1 output
RS-485	Pan / Tilt / Zoom camera communication		
USB Port	2 ports		
Mouse	USB mouse included		
IR Remote Controller	Included		
AVAILABLE STORAGE			
HDD Support	SATA HDD x 3 (Max. 1TB each)	SATA HDD x2 (Max. 1TB each)	SATA HDD x2 (Max. 1TB each)
	or	or	or
	SATA HDD x2 + DVD writer	SATA HDD x1 + DVD writer x1	SATA HDD x1 + DVD
DVD Writer	optional		
OSD			
Display Division	1,4,9,13,16	1,4,9	1,4
Title	14 characters		
RECORDING			
Video Compression	H.264		
Audio Compression	ADPCM		
Resolution	720x480, 720x240, 360x240 (NTSC)		
Frame Rate	120, 240, 480 (NTSC)	60, 120, 240 (NTSC)	60, 120, 120 (NTSC)
Quality	Highest, High, Normal, Basic, Low		
Record Mode	Manual, Schedule, Event (motion detection/sensor)		
Pre-Alarm Recording	16MB (around 10 sec)		
Post-Alarm Recording	1-999 sec		
Motion Detection	22X15 (sensitivity 0~10)		
PLAYBACK			
Search Mode	Time, Event		
Playback Speed	fast forward/backward 2X/4X/8X/16X/32X/64X slow forward/backward 1/2X, 1/4X, 1/8X, 1/16X		
Backup Mode	USB flash drive / Network / Optional DVD media		
NETWORK			
Network Compression	H.264		
Network Software	Internet Explorer / CMS / 3G Mobile Phone		
Network Users	5		
Remote Notification	Email message		
Service	TCP/IP, SMTP, DHCP, DDNS, PPPoE		
OTHER			
Daylight Savings	YES		
Password	5 users including 1 administrator; selectable authority		
Event List	10000		
Key Lock	YES		
Firmware Update	USB device		
Dimension	17"(W) x 2.75"(H) x 14.25" (D)		
Power Source	110VAC power supply included		
Operating Environment	30 to 80% RH; 41° F ~ 104° F		
Warranty	One year parts & labor, four years hard drive		
In Box	DVR, optical mouse, power supply, IR remote, software CD, & owner's manual		